



Declaration of performance: 2013-3
VO (EU) No. 305/2011 of March 2011

V&B Fliesen GmbH – Rotensteiner Weg – 66663 Merzig

EN 14411:2012 - Annex L “Requirements for dry-pressed ceramic tiles and panels of Group BIII ($E_b > 10\%$)”

Scope:



Wall coverings indoor for buildings and industrial buildings

Declared performance:

Main characteristics	performance	harmonized technical specification
Fire behaviour	Class A1	EN 14411: 2012
Modulus of rupture in N/mm ²	≥ 12 N/mm ² (Tile strength ≥ 7.5mm) ≥ 15 N/mm ² (Tile strength < 7.5mm)	EN 14411: 2012
Durability for		
- Usage indoor:	passed	EN 14411: 2012
Composite strength / Adhesion		
- cementitious mortar Type C2 - dispersion adhesives - Reaction resin adhesives	≥ 0,5 N/mm ² ≥ 1,0 N/mm ² ≥ 2,0 N/mm ²	EN 12004:2017; 4.1 EN 12004:2017; 4.2 EN 12004:2017; 4.3
- Mortar	No performance determined	Not testing
Thermal shock resistance	passed	EN 14411: 2012
Lead and cadmium release		
- Cadmium - Lead - other	No performance determined	EN 14411: 2012



ISO 9001
ISO 14001
OHSAS 18001
BUREAU VERITAS
Certification

