

Declaration of performance

VO (EU) no. 305/2011 of 9 March 2011

No.: 2021-5

Identification code of the product type: Dry-pressed ceramic tiles with water absorption $0.5\% \le E_b \le 3\%$, group Bl_b Purpose of use: Relevant clauses for ceramic tiles used for floorings for internal and external floorings, including stair treads in buildings and industrial buildings Relevant clauses for ceramic tiles used for walls for internal and external walls for buildings and industrial buildings Manufacturer: V&B Fliesen GmbH **Rotensteiner Weg** D-66663 Merzig Assessment and Verification of Constancy System 4 of Performance (AVCP): Harmonized standard for construction BS 14411:2012 products:

Declared performance:

| Main characteristics | Performance | | Harmonized technical specification |
|---|--|--|---|
| Reaction to fire | Class A1 / A1 _{FL} | | BS 14411: 2012 |
| Breaking strength in N | ≥ 1100 N (Tile strength ≥ 7,5mm) ≥ 700 N (Tile strength < 7,5mm) | | BS 14411: 2012 |
| Durability for | · · · · · · · · · · · · · · · · · · · | | |
| Indoor application Outdoor application Freeze-thaw-cycles resistance | passed | | BS 14411: 2012 |
| Tactility *** | No performance determined | | Tested in accordance with CEN/TS 15209:2008 |
| Composite strength / Adhesion | | | |
| cementitious mortar Type C2 | ≥ 0,5 N/mm² | | BS 14411: 2012 |
| - dispersion adhesives | No performance determine | ned | BS 14411: 2012 |
| Reaction resin adhesives | No performance determine | ned | BS 14411: 2012 |
| - Mortar | No performance determine | ned | Not tested |
| Thermal shock resistance | passed | | EN 14411: 2012 |
| Anti-Slip resistance ** | Ramp test | Shoes 0° - > 35° Barefood 0° - > 24° | Tested in accordance with EN 16165:2021 |
| | Pendulum friction test- PTV | 0 – 36+ | |
| | Friction coefficient with GMG 200 | 0 - >45µ | |
| Lead and cadmium release | | | |
| - Cadmium | | | |
| - Lead - Other | No performance determin | ned | BS 14411: 2012 |
| ** Only necessary when required by correspond overview *** (only for tactile floorings, meaning if requested | | | |

The performance of the product is in conformity with the performance declared above. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Dr. Jörg Schwall (Managing Director)